

REMOVE DEAD AND DAMAGED BRANCHES BY PRUNING ACCORDING TO RECOGNIZED HORTICULTURAL PRACTICES. DO NOT CUT LEADER.

RUBBER HOSE SECURED WITH 12 GAUGE PLIABLE GALVANIZED WIRE.

TWO STAKES PER TREE

BRANCH HEIGHT (MIN. 6')

REMOVE BURLAP FROM TOP 1/3 OF BALL.

WRAPPING

FINISHED GRADE OF PARKWAY SLOPE 2% FROM SIDEWALK TO CURB

STREET TREE (MIN. 2" CALIPER)

SET CROWN OF ROOT BALL 2" BELOW FINISHED GRADE

MULCH: BARK OR WOODCHIPS (MIN. 3")

CREATE SOIL SAUCER WITH TOPSOIL (MIN. 6")

SIDEWALK

2%

ROAD

2%

PLANTING SOIL

SUBSOIL

ROOT BALL

COMPACT SUBSOIL TO FORM PEDESTAL TO PREVENT SETTLING

DRIVE STAKES INTO UNDISTURBED SUBSOIL (12" MIN.)

TREE PLANTING IN PARKWAYS

ENGINEERING DEPARTMENT
1924 COUNCIL STREET
P.O. BOX 326
FOREST GROVE, OR 97116

